PQI

siegling extremultus

NEW

Product quick info

UR 20U-15 HC+ Pro GSTR/FSTR black/green



Sketch of cross-section (not actual size)

Applications

- AOI (Automated Optical Inspection) process in Semi-conductor, chip mounter and photovoltaics industries
- Conveying of electronic goods
- Conveying of photovoltaic wafers
- Drag belts
- Machine tapes

Properties/Advantages

- Elastic belt design makes fitting easy and exhibits very stable tracking behavior
- Homogenous belt design => no risk of contamination by fibers
- Highly conductive Plus (HC+), conductivity in all three spatial directions
- Special top coating (Pro), with extremely high grip properties for precise positioning
- Suitable for extremely small drum diameters

Basic technical data

Top face	Ultra High Grip, FSTR
Friction coating	Polyurethane, GSTR
Article no.	855670
d_{min} [mm]	10
Total thickness [mm]	1.45
F_W value [N/mm width]	0.24
Weight [kg/m²]	1.45

Product Quick Info | EN | 07.2025
FMS · Reproduction of text or parts thereof only with our approval. Modifications reserved.

Forbo Siegling GmbH
Lilienthalstrasse 6/8, D-30179 Hannover
Phone +49 511 67 04 0
www.forbo-siegling.com, siegling@forbo.com